

STIHL PLATINUM BAR & CHAIN OIL

Packaged for Stihl Incorporated, 536 Viking Drive, Virginia Beach, VA 23452



Safety Data Sheet

Conforms to HCS 2012 (29 CFR 1910.1200)

Section 1. Identification

Product identifier

Product Name: STIHL PLATINUM BAR & CHAIN OIL

Other names: F-4

Part/Product Number(s): 0781-516-5001, 0781-516-5003, 0781-516-5005, 0781-516-5006, 0781-516-5007, 7010-871-181, 7010-871-0211

Material Use: Bar and chain oil, lubricant

Uses advised against: Not for internal engine use.

Manufacturer: Omni Specialty Packaging, LLC
10399 Hwy 1 South
Shreveport, LA 71115
1-318-524-1100

Issuing date: May 8, 2015

Revision date: June 2, 2015

Revision number: 001

Company contact: OMNI EHS Department; E-Mail: sds@osp.cc; Contact phone: 318-524-1100
(Monday-Friday, 8:00 AM – 4:00 PM, CST)

In case of emergency : CHEMTREC: Within USA and Canada: 1 (800) 524-9300 (24/7)
CHEMTREC Outside USA and Canada: +1 703-527-3887 (24/7)

Section 2. Hazards Identification

OSHA/HCS Status: This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

GHS Classification of the Substance or Mixture: Not classified

GHS Label Elements

Hazard pictograms: None

Signal word: None

Hazard statement: None

Precautionary statements

General: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention: Not applicable

Response: Not applicable

Storage: Not applicable

Disposal: Not applicable

Hazards not otherwise classified (HNOC): Defatting to the skin.

Section 5. Fire-Fighting Measures

Uniform Fire Code: Class IIIB

Flash Point: >93.3°C (>200°F)

Extinguishing Media

Suitable Media: In case of fire, use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water fog, alcohol resistant foam, dry chemical, carbon dioxide (CO₂) extinguisher or spray.

Unsuitable Media: CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical:

Keep product and empty container away from heat and sources of ignition as product will burn. Contact with strong oxidizers may cause fire. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be contained, prevented from being discharged to any waterway, sewer or drain and disposed of in accordance with local regulations.

Hazardous Combustion Products: Combustion products may include the following: Carbon dioxide (CO₂) Carbon monoxide (CO), and Nitrogen oxides.

Protection of Fire Fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Put on appropriate personal protective equipment (see Section 8). Floors may be slippery; use care to avoid falling.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Ensure adequate ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material onto soil or into waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). See Section 12 for ecological information.

Methods and materials for containment and cleaning up

Small Spills: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spills: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

NOTE: If RQ (Reportable Quantity) is exceeded or if spills enter a body of water, report immediately to the USEPA's National Response Center at (800) 424-8802. Check with your local and state regulators regarding their reporting requirements.

Section 7. Handling and Storage

Precautions for safe handling

- Protective measures:** Safety glasses with side shields. Eye protection and face shield should be used if material is used under conditions that increase the chances of splattering. Put on appropriate personal protective equipment (see Section 8). Keep out of reach of children.
- Advice on general occupational hygiene:** Do not get in eyes, on skin or on clothing. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas.
See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities:** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, strong oxidizing agents (see Section 10) and food and drink. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Avoid contaminating soil or releases into sewage or drainage systems and bodies of water.
- Bulk material handling:** Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient.

Section 8. Exposure Controls/Personal Protection

Control parameters

Occupational Exposure Limits

Chemical name	ACGIH		OSHA		NIOSH	
	TLV	STEL	PEL	STEL	TWA	Ceiling
Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15-C50)	5 mg/m ³ (mist)	10 mg/m ³ (mist)	5 mg/m ³ (mist)	—	—	—

- Appropriate engineering controls:** Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emergency shower and eyewash station.
- Environmental exposure controls:** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
- Eye/Face Protection:** Wear safety glasses with side shields. A face shield may be necessary under some conditions.
- Skin and Body Protection**
- Hand protection:** Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. Consult your supervisor or Standard Operating Procedure (SOP) for special handling instructions.
- Body protection:** No protective equipment is needed under normal use conditions. For non-routine tasks, personal protection equipment for the body should be selected based on the task being performed and the risks involved.
- Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.

Respiratory protection:

No respiratory protection is normally required. If user operation generates an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from measured concentrations of this material. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Section 9. Physical and Chemical Properties

<u>Appearance</u>	<u>(Typical or Target)</u>
Physical State:	Liquid
Color:	Straw colored
Odor:	Petroleum like
Odor threshold:	Not available
pH:	Not applicable
Boiling Point:	Not available
Flash Point (Closed cup):	>93.3°C (>200°F) (Typical or Target)
Evaporation rate (Butyl acetate = 1):	Not available
Flammability (solid, gas):	Not applicable. Based on - Physical state
Flammable) Limit in Air	Not available
Vapor pressure:	Not available
Vapor density (Air = 1):	>1
Relative density:	0.90 - 0.92 g/l at 15°C (Typical or Target)
Solubility:	In soluble in water
Partition coefficient (n-Octanol/water):	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity – Kinematic (cSt (mm ² /s)@ 40°C):	120 – 173
Viscosity – Kinematic (cSt (mm ² /s) @ 100°C):	10 – 12.4
VOC %:	0 %

Section 10. Stability and Reactivity

Reactivity:	Not reactive under normal storage conditions
Chemical stability:	Stable under normal storage conditions
Possibility of hazardous reactions:	None under normal processing.
Hazardous polymerization:	Hazardous polymerization does not occur.
Conditions to avoid:	Heat, flames and sparks.
Incompatible materials:	Oxidizing agents and open flames.
Hazardous decomposition products:	May include: Fumes, Oil vapors, Smoke, Carbon Oxides (including carbon monoxide and carbon dioxide), Aldehydes, Nitrogen oxides, and incomplete combustion products.

Section 11. Toxicological Information

Information on toxicological effects

Basis for Assessment: Information given is based on product data, a knowledge of the components and the toxicity of similar products.

Likely Routes of Exposure: Exposure may occur via skin absorption, skin or eye contact, inhalation, ingestion.

Substance/Mixture

<u>Acute Toxicity</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Inhalation LC50</u>
Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15- C50) Mixture - Typical	>2000 mg/Kg (rat)	>2000 mg/Kg (rabbit)	>2.18 mg/L (rat) 4h (mist)

Aspiration hazard: Not expected to be an aspiration hazard.

Skin Corrosion/Irritation:	No known significant effects or critical hazards.
Serious Eye Damage/Irritation:	No known significant effects or critical hazards.
Skin Sensitization:	No known significant effects or critical hazards.
Respiratory Sensitization:	No known significant effects or critical hazards.
Specific Target Organ Toxicity (Single Exposure) - STOT-SE:	No known significant effects or critical hazards.
Specific Target Organ Toxicity (Repeated Exposure) – STOT-RE:	No known significant effects or critical hazards.
Carcinogenicity:	No known significant effects or critical hazards.
Germ Cell Mutagenicity:	No known significant effects or critical hazards.
Reproductive Toxicity	No known significant effects or critical hazards.

Information on Toxicity Effects of Compounds

Lubricant Base Mineral Oil (Petroleum)

Mineral oils are known to cause cancer because of carcinogenic components (e.g. Benzene). The lubricant base mineral oils in this product have been highly refined by a variety of processes including severe solvent extraction, severe hydro cracking or severe hydro treating to reduce aromatics and improve performance characteristics. The oils in the product meet the IP-346 criteria of less than 3 percent PHA's and are not considered to be a carcinogen by the International Agency for Research on Cancer.

None of the oils in this product requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as: carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

Section 12. Ecological Information

The information is based on data available for the material, the components of the material, and similar materials.

Ecotoxicity: No testing has been performed by the manufacturer. Ecotoxicity hazard is based on an evaluation of data for the components or a similar material. Not expected to be harmful to aquatic organisms.

Mobility: Base oil component – Low solubility and floats on water and is expected to migrate from water to land. Expected to partition to sediment and wastewater solids.

Persistence and degradation

Biodegradation: The material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material.

Bioaccumulative potential

Bioaccumulation: This product is not expected to bioaccumulate through food chain in the environment.

Other adverse effects: No known significant effects or critical hazards.

Other ecological information: Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal Considerations

Disposal recommendations based on material supplied.

Waste treatment methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Consult the appropriate state, regional, or local regulations for additional requirements. The generation of waste should be avoided or minimized wherever possible.

Product waste: Significant quantities of waste product residues should not be disposed of via the sanitary sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-

recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Incineration or landfill should only be considered when recycling is not feasible. Oil collection services are available for used oil recycling.

Contaminated packaging: Empty containers or liners may retain some product residues and could pose a potential fire and explosion hazard. Do not cut, puncture, or weld containers.

Other information: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport Information

General information: Petroleum Lubricating oil - Not regulated.

	DOT Classification	IMDG	IATA
Bar & Chain Oil	Not Regulated	Not Regulated	Not Regulated

Special precautions for user: Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory Information

United States Regulations

United States Inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304: No products were found.

SARA 311/312: Immediate (Acute) Health Effects: No
 Delayed (Chronic) Health Effects: No
 Fire Hazard: No
 Sudden Release of Pressure Hazard: No
 Reactivity Hazard: No

SARA 313:

The following components of this material are found on the EPCRA 313 list:
 None

Supplier notification: This product does not contain any hazardous ingredients at or above regulated thresholds.

CWA (Clean Water Act): This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA: This material, as supplied, does not contain any substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

State Regulations

Massachusetts: None of the components are at or above regulated thresholds.
New Jersey: None of the components are at or above regulated thresholds.
Pennsylvania: None of the components are at or above regulated thresholds.
California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.
 None

Canada

WHMIS Hazard Class: Not classified. This Product Is Not Controlled Under WHMIS (Canada)

International Chemical Inventories:

All components comply with the following chemical inventory requirements: DSL (Canada)

Section 16. Other Information

NFPA Rating:	Health Hazard – 1	Flammability – 1	Instability/Reactivity – 0
HMIS Rating:	Health Hazard – 1	Flammability – 1	Physical Hazards – 0

(NFPA & HMIS Hazard Rating Key: 0 - Minimum Hazard; 1 - Slight Hazard; 2 - Moderate Hazard; 3 - High Hazard; 4 - Extreme Hazard; * - Chronic Hazard Indicator, & PPE - Personal Protective Equipment Index A to L. These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS or Hazardous Material Identification System).

Key to abbreviations:

OSHA = Occupational Safety and Health Administration

ACGIH= American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service Registry Number

cSt = Centistroke (mm²/s)GHS = Global Harmonized System of Classification and Labeling
Of Chemicals.

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet

STEL = Short term exposure Limit

UN = United Nations

UN Number = United Nations Number, a four digit number
assigned by the United Nations Committee of Experts on
the Transportation of Dangerous Goods**Prepared By: OMNI Specialty Packaging EH&S Department****Revision Date: June 2, 2015****Status: Final****Revision Note: Revision 001 of OSHA GHS SDS format.****Consumer Product Improvement Act of 2008, General Conformity Certification**

For Consumer Product Packages: This product has been evaluated and is certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission. Where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No testing is required to certify compliance with the provisions. The date of the manufacturing is stamped on the product container.

Disclaimer

All reasonably practicable steps have been taken to ensure the information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

End of Safety Data Sheet