FM MUPD Compliance

Samuel Cabot Inc.

Hale Street
...huryport, MA 01950
00-US STAIN
:. (978) 462-2720

33360 Central Avenue
Union City, CA 94587
Tel. 888-WC STAIN
Fax. (510) 477-9615

Cabot®

Material Safety Data Sheet

TITY (As Used on Label and List) 3457, 3458, 3459 Australian Timber Oil

ction I

gency Telephone Number: Call local emergency medical services.
Call Chem-Tel 1-800-255-3924.

Prepared: October 2000 Signature of Preparer (Optional)

ction II - Hazardous Ingredients/Identity Information

rdous Components (Specific Chemical Identity; Common Name(s))	CAS #	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
roleum Distillates (MSL*)	8052-41-3	100 ppm TWA	100 ppm TWA		

ese products contain a Maximum Volatile Organic Compound (V.O.C.) content of 550 grams per liter (4.6 pounds per gallon).

SL - Massachusetts Substance List

ction III - Physical/Chemical Characteristics

n Point	> 300°F		Specific Gravity (H2O = 1)	0.86
Pressure (mm Hg.)	@ 68°F	< 5mm Hg	Melting Point	Not applicable
Density (AIR = 1)		> 1	Evaporation Rate (Butyl Acetate = 1)	< 1

ility in Water: Negligible

arance and Odor: Colored liquids - solvent odor

ction IV - Fire and Explosion Hazard Data

Point (Method Used) > 100°F (TCC) Flammable Limits LEL 1.0 UEL 6.0

uishing Media: Water fog, foam, dry chemical, CO_2, Class B fire extinguishers.

al Fire Fighting Procedures

not use a direct water stream. Recommend self-contained breathing apparatus for firefighters. Water may be used to cool closed tainers. Moderate Fire Hazard.

ual Fire and Explosion Hazards

ss II combustible liquid. *Closed containers may explode when exposed to extreme heats.* Combustion may produce hazardous es. Danger: - Rags, steel wool, lambs wool or waste soaked with Australian Timber Oil may spontaneously catch fire if improperly arded. *Immediately after each use, place rags, steel wool, lambs wool or waste in a sealed, water-filled metal container.*

Section V - Reactivity Data

Stability: Unstable; Stable X

Conditions to Avoid: Storage near heat, sparks, flame, electrical equipment & other ignition sources.

Incompatibility (Materials to Avoid): Avoid contact with strong oxidizing agents.

Hazardous Decomposition or Byproducts: Fumes, smoke, carbon dioxide, carbon monoxide, various hydrocarbons.

Hazardous Polymerization: May Occur X; Will Not Occur

Conditions to Avoid: Soak oily rags and cloths in water after use to avoid spontaneous combustion.

Section VI - Health Hazard Data

Routes of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (Acute and Chronic): May be irritating to eyes, skin, nose, throat; chronic dryness and dermatitis to skin. Acute and chronic inhalation may cause headaches, dizziness, nausea, fatigue. Ingestion may cause irritation and vomiting.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Signs and Symptoms of Exposure: Irritation to eyes, skin, respiratory tract. Headaches, dizziness, nausea, fatigue.

Medical Conditions Generally Aggravated by Exposure: Persons with breathing difficulties, skin sensitivities, eye sensitivities.

Emergency and First Aid Procedures

EYES: Flush with water for 15 minutes. Call physician. SKIN: Wash affected areas with soap and water. Remove contaminated clothing. INHALATION: Remove to fresh air. Restore normal breathing. INGESTION: Do not induce vomiting. Drink plenty of milk or water. Call physician immediately.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Remove ignition sources. Ventilate area. Dike and contain spill with inert material (i.e. sand, earth). Add absorbent material and remove to closed containers for disposal. Wear protective clothing.

Waste Disposal Method: Incinerate and/or dispose of in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing

Do not use or store near heat, possible ignition sources, or food products. Keep containers closed when not in use. Keep away from children and animals.

Section VIII - Control Measures

Respiratory Protection (Specify Type): Use approved vapor/mist respirator in areas of poor ventilation.

Ventilation: Local Exhaust In areas of poor ventilation Special None known Other None known

Mechanical (General): If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

Protective Gloves: Neoprene or rubber gloves if necessary. Eye Protection: Splash proof safety goggles or glasses.

Other Protective Clothing or Equipment: Wear a vapor/mist respirator during spray applications.

Work/Hygienic Practices: Read label on can before using. Do not reuse empty containers. Not intended for interior surfaces. For exterior use only. Furniture coated with Australian Timber Oil may be stored indoors.